

REPEATING COILS

Code	Former Spec	Shield	Impedance Ratio Ohms	Max DC Resistance Ohms		Min Induct Low Wdgs Henrys	Frequency Range	Dimensions - Inches			Wt Lbs	Low Windings	High Windings	Remarks
				Low Mdg	High			Length	Width	Height				
94AA	D-156587	-	600:300	12.5	31	.16 (3-4) (7-8)	200-3500cps	3-1/8	1-23/32	4-1/4	2.2	(2-1)(6-5)	(4-3)(8-7)	FIG. K
96B	D-79683	-	1:160,000	0.23	315	1.6 (3-4)	16-425 cps	3-3/16	2-5/8	3-17/32	3.5	(1-2)	(3-4)(5-6)	FIG. T
100A	Half 62A	-	1:1 ratio	50	52	1.04	Voice	3-7/8	2-1/16	3-15/16	4.0	(1-2)(5-6)	(3-4)(7-8)	
100B	Half 62C	-	1:1.62 ratio	48	64	0.64	Voice	3-7/8	2-1/16	3-15/16	4.0	(1-2)(5-6)	(3-4)(7-8)	
102A	Half 75A	-	1:1 ratio	50	52	2.6	Voice	3-7/8	2-1/16	3-15/16	3.1	(1-2)(5-6)	(3-4)(7-8)	
102B	Half 75C	-	1:1.62 ratio	29	51	1.6	Voice	3-7/8	2-1/16	3-15/16	3.1	(1-2)(5-6)	(3-4)(7-8)	
107A	D-87301	E	600:600	13.4	15.0	0.68	5-30 ke	4-9/32	2-9/16	4-3/8	4.5	(1-2)(5-6)	(3-4)(7-8)	
108A		-	600:900	7.7	9.9	1.6	200-3500cps	3-9/32	1-11/16	3-7/16	2.3	(2-1)(6-5)	(4-3)(8-7)	FIG. J
108C		-	1420:1600	20.0	17.4	4.4	200-3500cps	3-9/32	1-11/16	3-7/16	2.3	(2-1)(6-5)	(4-3)(8-7)	FIG. J
111A		E	600:40	2.2	29.3	1.28	35-8500cps	4-3/16	2-9/16	4-5/32	4.5	(1-2)(5-6)	(3-4)(7-8)	FIG. U
111C	D-87653	E	600:600	40.0	40.0	27.0	35-8000cps	4-3/16	2-9/16	4-5/32	4.5	(1-2)(5-6)	(3-4)(7-8)	FIG. U
111D	D-92301	-	1200:600	6.0	12.0	12.0 high wdg	250-2750 cps	4-3/16	2-9/16	4-5/32	4.5	(3-4)(7-8)	(1-2)(5-6)	FIG. U
119B	D-91918	-	600:37	2.3	40	27.0 high wdg	35-8000cps	4-9/32	2-9/16	4-3/8	4.0	(1-2)(5-6)	(3-4)(7-8)	
119C	D-91915	E	1:1.15 ratio	50	55	27.0	35-8000cps	4-9/32	2-9/16	4-3/8	4.0	(3-4)(7-8)	(1-2)(5-6)	
119D		-	218:600	9.8	22.8	27 (4-7)	35-8000cps	4-9/32	2-9/16	4-3/8	4.0	(2-1)(6-5)	(4-3)(8-7)	
119E		E	600:600	40	40	27.0	35-8000cps	4-9/32	2-9/16	4-3/8	4.5	(1-2)(5-6)	(3-4)(7-8)	
119F		-	1200:600	6	12	12.0 high wdg	250-2750 cps	4-9/32	2-9/16	4-3/8	4.0	(4-3)(8-7)	(2-1)(6-5)	
120C		-	900:900	12.7	17.8	0.55	Voice	3-1/8	1-23/32	4-1/4	2.2	(2-1)(5-5)	(4-3)(8-7)	FIG. K
120D		-	1350:900	12.7	29.2	0.55	Voice	3-1/8	1-23/32	4-1/4	2.2	(4-3)(8-7)	(2-1)(6-5)	FIG. K
120E		-	600:900	11.5	12.7	0.55 high wdg	Voice	3-1/8	1-23/32	4-1/4	2.2	(2-1)(6-5)	(4-3)(8-7)	FIG. K
120F		-	600:1500	5.7	19	0.32	Voice	3-1/8	1-23/32	4-1/4	2.2	(2-1)(6-5)	(4-3)(8-7)	FIG. K
120G		-	600:900 600:1500	5.7	19	0.32	Voice	3-1/8	1-23/32	4-1/4	2.2	(2-1)(6-5)	{4L-3}(8-7L) {4H-3}(8-7H)	FIG. K
120H	Similar to 120C but has crosstalk requirements													
120J	Similar to 120D but has crosstalk requirements													
120K	Similar to 120E but has crosstalk requirements													
120L	Similar to 120F but has crosstalk requirements													